


Gelijkzijdig L-profiel (koudgewalst)

6m

Afmetingen en toleranties: EN 10162:2003

Profiel (HxBxT)	Voorraad (blank)	Handelsgewicht (kg/m)	Dimensies			
			H=B	T	R1	R2
20x20x1,5		0,45	20	1,5	1,5	3,0
20x20x2	✓	0,59	20	2	2,0	4,0
20x20x3		0,84	20	3	3,0	6,0
25x25x2	✓	0,75	25	2	2,0	4,0
25x25x3		1,08	25	3	3,0	6,0
30x30x2		0,91	30	2	2,0	4,0
30x30x3		1,32	30	3	3,0	6,0
35x35x2		1,09	35	2	2,0	4,0
35x35x3		1,56	35	3	3,0	6,0
40x40x2		1,23	40	2	2,0	4,0
40x40x3	✓	1,80	40	3	3,0	6,0
40x40x4		2,39	40	4	4,0	8,0
50x50x3	✓	2,28	50	3	3,0	6,0
50x50x4		2,99	50	4	4,0	8,0
50x50x5		3,67	50	5	5,0	10,0
60x60x3		2,76	60	3	3,0	6,0
60x60x4		3,63	50	4	4,0	8,0
80x80x5	✓	6,07	80	5	5,0	10,0
100x100x5	✓	7,67	100	5	5,0	10,0



✓ is op voorraad in staalsoort S235, andere profielen zijn verkrijgbaar op bestelling



Metaleuven ijzermagazijn
Aarschotsesteenweg 106
B-3012 Wilsele
info@ijzermagazijn.be

Openingstijden:

Maandag tot donderdag

8:00 tot 12:00 - 12:30 tot 16:30

Vrijdag

8:00 tot 12:00 - 12:30 tot 14:30